

TA3 D S060 - 1360 005

**Product codes:**

Reference: 1360 005

Product short description:

Trolley with lifting hook and rubber wheels assembled with Diesel engine and self-priming centrifugal pump Type Victor Pumps S 60 (Q max: 45 m³/h; H max: 50 m) with following features:

- Hatz Diesel engine
- Close-coupled
- Stage V (EU)
- Manual start
- PinoPumps standard stainless steel name plate with product name and serial number

Product features:

Main Features
Pump Flow Rate: max 45 m ³ /h (750 l/min)
Pump head: max 50 m
Max. Solids Handling: 17 mm
Self-priming: ★★★★★☆
Heavy-duty: ★★★★★☆
Frame: TA3 single-axle trolley
Suitable for the EU sales area: Yes
Suitable for the US sales area: No

Frame**Type of Tyre:** Solid rubber wheels with tractor profile**Suitable for solid ground:** Yes**Suitable for muddy and sandy terrains:** Yes**Lifting hook:** Yes**Can be moved by hand:** Yes**Can be towed with a vehicle:** No**Towing bar with hook:** No**Document box prepared for lock:** No**Tool box prepared for lock:** No**Tank on engine:** Yes**Tank integrated in frame:** No**Tank Capacity:** 5 l**Pump****Type of Pump:** Self-priming centrifugal pump**Pump manufacturer:** Victor Pumps**Suction port:** 2"**Discharge port:** 2"**Type of ports:** Female Thread BSP**Type of self-priming:** Wet-prime**Vaccum pump:** No**Inspection cover for the impeller:** Yes**Filling port:** Yes**Drain Port:** Yes**Plug for Vacuometer:** Option**Plug for the Manometer:** Option**Material of casing:** Cast iron**Material of impeller:** Cast iron**Material of wear plate:** Steel**Material of shaft:** Stainless steel AISI316**Material of non-return valve:** NBR**Shaft sealing:** YCV Mechanical Seal with Grease Lubrication in SiC/SiO₂/FKM (Viton®) on Stainless Steel Sleeve**Performance data****Max vacuum with water:** max 8 m (9, 5 m for 10 min)**Max vacuum with air:** max 8, 5 m**Product gallery:**

