

GA2 Q S081 - 2281 001



Product codes:

Reference: 2281 001

Product short description:

Carrying frame for 2 people assembled with gasoline engine and self-priming centrifugal pump Type Victor Pumps S 81 (Q max: 95 m³/h; H max: 36 m) with following features:

- Honda Diesel engine
- Close-coupled
- Stage V (EU)
- Manual start

Product features:

Main Features
Pump Flow Rate: max 95 m ³ /h (1580 l/min)
Pump head: max 35 m
Max. Solids Handling: 36 mm
Self-priming: ★★★★★☆
Heavy-duty: ★★☆☆☆
Frame: Carrying frame for 2 persons
Suitable for the EU sales area: Yes
Suitable for the US sales area: No

Frame

Can be moved by hand: Yes

Can be towed with a vehicle: No

Towing bar with hook: No

Document box prepared for lock: No

Tool box prepared for lock: No

Tank on engine: Yes

Tank integrated in frame: No

Tank Capacity: 6, 1 l

Pump

Type of Pump: Self-priming centrifugal pump

Pump manufacturer: Victor Pumps

Suction port: 3"

Discharge port: 3"

Type of ports: Female Thread BSP

Type of self-priming: Wet-prime

Vaccum pump: No

Inspection cover for the impeller: Yes

Filling port: Yes

Drain Port: Yes

Plug for Vacuometer: No

Plug for the Manometer: No

Material of casing: Aluminum

Material of impeller: Stainless steel

Material of wear plate: Steel

Material of non-return valve: NBR (Nitrile)

Shaft sealing: GYV Graphite/Silicon carbide/FKM

Drive

Type of drive unit: Gasoline engine

Drive Manufacturer: Honda

Drive code: GX390

Exhaust gas regulation: Stage V

Manual Start: Yes

Electric start: No

No. of Cylinder: 1

Strokes: 4-stroke

Displacement: 389 cm³

Rated Power: 8, 7 kW (11.7 HP)

Maximal Rotation: 3600 rpm

Cooling: Air cooled

Performance data

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 8, 5 m

Additional Features

Switchboard: No

Paint: RAL3003 ruby red

External Dimensions (L x W x H): 834 x 561 x 510 mm

Net Weight: 56 kg

Product gallery:





