


## TS2 D S100 - 1810 002

### Product codes:

Reference: 1810 002



### Product short description:

Trailer with integrated tank, towing eye, lifting hook and tyres assembled with Diesel engine and self-priming centrifugal pump Type Victor Pumps S100 (Q max: 150 m<sup>3</sup>/h; H max: 30 m) with following features:

- Hatz Diesel engine
- Close-coupled
- Stage V (EU)
- Electric start
- Battery 50 Ah
- Frame with integrated 35 ltr. fuel tank (Type 4510) and battery-cover
- Tool box prepared for lock (34x15x30 cm)


### Product features:

Main Features
<b>Pump Flow Rate:</b> max 150 m <sup>3</sup> /h (2500 l/min)
<b>Pump head:</b> max 30 m
<b>Max. Solids Handling:</b> 36 mm
<b>Self-priming:</b> ★★☆☆☆
<b>Heavy-duty:</b> ★★☆☆☆
<b>Frame:</b> Frame with integrated tank

**Suitable for the US sales area:** No**Suitable for non regulated sales areas:** Yes**Frame****Type of Tyre:** 10" Tyres with Tractor Profile**Suitable for solid ground:** Yes**Suitable for muddy and sandy terrains:** Yes**Lifting hook:** Yes**Can be moved by hand:** Yes**Can be towed with a vehicle:** Yes**Towing bar with hook:** Yes**Document box prepared for lock:** Yes**Tool box prepared for lock:** No**Tank on engine:** No**Tank integrated in frame:** Yes**Tank Capacity:** 35 l**Pump****Type of Pump:** Self-priming centrifugal pump**Pump manufacturer:** Victor Pumps**Suction port:** 4"**Discharge port:** 4"**Type of ports:** Female Thread BSP**Type of self-priming:** Wet-prime**Vaccum pump:** No**Inspection cover for the impeller:** Yes**Filling port:** Yes**Drain Port:** Yes**Plug for Vacuometer:** Option**Plug for the Manometer:** Option**Material of casing:** Cast iron**Material of impeller:** Ductile Cast-iron**Material of wear plate:** Steel**Material of shaft:** Stainless steel AISI420**Material of non-return valve:** NBR (Nitrile)**Shaft sealing:** WWN tungsten carbide tungsten carbide NBR**Drive****Type of drive unit:** Diesel**Drive Manufacturer:** Hatz**Exhaust gas regulation:** Stage V

<b>No. of Cylinder:</b> 1
<b>Strokes:</b> 4-stroke
<b>OPS Engine Protection by Pino:</b> No
<b>Maximal Rotation:</b> 3000 rpm
<b>Cooling:</b> Air cooled
<b>Performance data</b>
<b>Max vacuum with water:</b> max 8 m (9, 5 m for 10 min)
<b>Max vacuum with air:</b> max 8, 5 m
<b>Additional Features</b>
<b>Battery Size:</b> 80 Ah
<b>Battery-cover:</b> Yes
<b>Switchboard:</b> Yes
<b>Indicators on the panel:</b> Oil Pressure, Power-Battery Supply
<b>Paint:</b> RAL1006 maize yellow
<b>External Dimensions (L x W x H):</b> see dimensions
<b>Net Weight:</b> see dimensions

**Product gallery:**



Performance **PINO PUMPS** T7120-8861 44 0 267

### S100 G12ZH

Leistung: 100 kW  
Anzahl: 12  
Feststoffgröße: 32 mm Ø  
Saughöhe: 8 m  
Umdrehung: 3600/min  
Vorgabe: V100/8

